

# MOLL-MOTOR

Silniki o sprawności premium IE3 1500obr/min, S1, IP55, klasa iz. F  
temp. pracy -20°C do +40°C, klimat umiarkowany, RAL7020 mat.

PN-EN 60034-1



typ silnika		obroty (obr/min)	moc (kW)	prąd znam. (A)	sprawność $\eta$	współ. mocy $\cos\varphi$	moment (Nm)	$M_s/M_n$	$I_s/I_n$	$M_b/M_n$	bezwładność	hałas Lw	waga
typ silnika	ilość bieg.										kgm2	dB(A)	(kg)
Y2PE-132M-4	4	1470	7,5	14,3	90,4	0,84	48,7	2,0	7,5	2,3	0,03982	71	66
Y2PE-160M-4	4	1470	11	20,4	91,4	0,85	71,5	2,2	7,7	2,3	0,08519	73	125
Y2PE-160L-4	4	1470	15	27,3	92,1	0,86	97,4	2,2	7,8	2,3	0,11158	73	143
Y2PE-180M-4	4	1475	18,5	33,5	92,6	0,86	120	2,0	7,8	2,3	0,16786	76	185
Y2PE-180L-4	4	1475	22	39,7	93,0	0,86	142	2,0	7,8	2,3	0,20652	76	195
Y2PE-200L-4	4	1480	30	53,8	93,6	0,86	194	2,0	7,8	2,3	0,31470	76	250
Y2PE-225S-4	4	1485	37	66,1	93,9	0,86	238	2,0	7,4	2,3	0,52242	78	300
Y2PE-225M-4	4	1485	45	80,2	94,2	0,86	289	2,0	7,4	2,3	0,61178	78	342
Y2PE-250M-4	4	1485	55	97,6	94,6	0,86	354	2,0	7,4	2,3	0,82935	79	391
Y2PE-280S-4	4	1485	75	129,0	95,0	0,88	482	2,0	6,9	2,3	2,11992	80	520
Y2PE-280M-4	4	1485	90	155,0	95,2	0,88	579	2,0	6,9	2,3	2,56340	80	632
Y2PE-315S-4	4	1485	110	187,0	95,4	0,89	707	2,0	7,0	2,2	3,62598	88	940
Y2PE-315M-4	4	1485	132	224,0	95,6	0,89	849	2,0	7,0	2,2	4,21024	88	1020
Y2PE-315L1-4	4	1485	160	271,0	95,8	0,89	1029	2,0	7,1	2,2	4,60495	88	1090
Y2PE-315L2-4	4	1485	200	334,0	96,0	0,9	1286	2,0	7,1	2,2	5,27395	88	1223
Y2PE-355M-4	4	1490	250	418,0	96,0	0,9	1602	2,0	7,1	2,2	7,24750	95	1723
Y2PE-355L-4	4	1490	315	526,0	96,0	0,9	2019	2,0	7,1	2,2	9,14300	95	1986

Zastrzegamy możliwość zmian technicznych

